

800h 825 Monel Alloy K500 925 926 Inconel 600 601 625 718 Nickel Alloy Steel **Plate**

Basic Information

- Place of Origin:
- Brand Name:
- Model Number: Monel K-500
- Minimum Order Quantity: 1-2 ton
- Price: negotiable carton box
- Packaging Details:
- Delivery Time: 15-20 days
- Payment Terms: Western Union, MoneyGram, T/T

China

Qingsen



Product Specification

- Type:
- Material:

• Shape:

• Width:

• Surface:

- Nickel Alloy Sheet Inconel840 (S33400), Inconel 686 (2.4606-N06686) Flat Sheet
- Certificate: ISO9001
- Cold Rolled/hot Rolled • Technology:
 - 1-50mm
 - 2B/BA/NO.1/NO.3/NO.4/8K/HL/1D
- Standard:
- Highlight:
- ASTM 825 Monel Alloy K500, 800h Monel Alloy K500, 718 Nickel Alloy Steel Plate

Our Product Introduction

Product Description

Incoloy 800h 825 925 926 Inconel 600 601 625 718 Nickel Alloy Steel Plate Monel 400 K500

| Inconel Alloy | Inconel840 (S33400), Inconel 686 (2.4606-N06686), Inconel725 | | | | | | |
|-------------------|--|--|--|--|--|--|--|
| | (NO7725), Inconel713C (2.4671), Inconel625 (2.4856), | | | | | | |
| | Inconel602ca(N06625), Inconel601 (2.4851), Inconel600 (2.4816), | | | | | | |
| | Inconel 690 (2.4642), Inconel617 (N06617), InconelX-750 (750), | | | | | | |
| | Inconel804, | | | | | | |
| | Inconel718 (2.4668). | | | | | | |
| Surface Finish | 2B, BA, NO.1, NO.4, 8K, HL, Embossing, Satin, Mirror, ect | | | | | | |
| Technique | Cold Rolled; Hot Rolled | | | | | | |
| | Hastelloy AlloyB-2/Hastelloy B-2 Alloy, Hastelloy AlloyB3/Hastelloy B3 | | | | | | |
| Hastelloy Alloy | Alloy, Hastelloy C-2000 Alloy/Hastelloy AlloyC-2000,Hastelloy C- | | | | | | |
| I lastelloy Alloy | 4/Hastelloy AlloyC-4/2. 4610, Hastelloy C-22/Hastelloy AlloyC22, | | | | | | |
| | Hastelloy AlloyC-276/Hastelloy C-276 Alloy. | | | | | | |
| Width | 1000mm, 1219mm, 1250mm, 1500mm,or as customer's request | | | | | | |
| Length | 2000mm,2438mm,3000mm,6000mm,or as as customer's request | | | | | | |
| Delivery Time | Normally 7-15 working days after the receipt of 30% deposit, or | | | | | | |
| | according to the quantity | | | | | | |
| Payment Terms | 30% TT for deposit,70% TT /70% LC at sight balance before shipment | | | | | | |
| | 20ft GP: 5898mm(Length)x2352mm(Width)x2393mm(High), Max. 25 | | | | | | |
| | Ton | | | | | | |
| Container Size | 40ft GP: 12032mm(Length)x2352mm(Width)x2393mm(High), Max. 25 | | | | | | |
| | Ton | | | | | | |
| | 40ft HC: 12032mm(Lengh)x2352mm(Width)x2698mm(High), Max. 25 | | | | | | |
| | Ton | | | | | | |
| Loading Port | Shanghai Port | | | | | | |
| Standard | JIS/SUS/DIN/ASTM/AISI/EN | | | | | | |
| Price Terms | FOB, EXW, CIF, CFR | | | | | | |
| Application | High temperature components such as turbine blades, guide vanes, | | | | | | |
| | turbine disks, | | | | | | |
| | high pressure compressor disks,machine manufacturing and | | | | | | |
| ppiloalion | combustion chambers | | | | | | |
| | used in the manufacture of aviation, naval and industrial gas turbines | | | | | | |

| Chemical Co | ompositior | 1 | | | | | | | | | | |
|-----------------------------------|--------------------------|----------|-----------|------------|-------------------------|------|------------|----------------|--------|--------------|-------|--|
| Grade | Ni% | Cu% | Fe% | 1 | Mn% | C% | | | , o | S% | | |
| Monel 400 | Min 63 | 28-34 | Max 2. | 5 1 | Max 2.0 | Max | ax 0.30 Ma | | x 0.50 | Max | 0.024 | |
| Monel 400 li | nternation | al Brand | | | | | | | | | | |
| USA | | | GE | | | | | UK F | | FR | FR | |
| UNS | | | SEW VDIUV | | | | | | BS | AF | NOR | |
| Monel 400 | Monel 400 N04400 W.Nr.2. | | | | 4360 NiCu30Fe | | | | NA 12 | Nu | 30 | |
| Physical Pro | perties | | | | | | | | | | | |
| Grade Density | | | | Me | | | | elting Point | | | | |
| Monel 400 8.83 g | | | | 3 g/cm3 13 | | | | 300 -1390 | | | | |
| Mechanical | Properties | | | | | | - | | | | | |
| Alloy Tensile Stren (Rm N/mm2) | | 0 | h | | d strength 0.2N/mm2) | | E | Elongation(A59 | | %) | НВ | |
| Monel 400 | 1onel 400 480 | | | 170 | | | | 35 | | | ≥331 | |
| Production S | Standard | | | | | | | | | | | |
| Bar | | Fo | orging | | Pipe | Pipe | | Sheet/Strip | | Welding Wire | | |
| Standard ASTM B164 A | | 64 AS | TM B56 | 4 | ASTM B165 | | AS | ASTM B127 | | ERNiCu-7 | | |

Monel K-500(UNS N05500)

| 化学成分 Chemical Composition | 合金 | % | 镍Ni | 铜Cu | 铁Fe | 铝AL | 碳C | 钛Ti | 猛Mn | 硅Si | 硫P |
|-------------------------------------|----------------------------------|---|---------------------------------|----------------------------------|------------------------------------|---------------------------------|-------------------------------------|----------------------------------|------------------------------------|-------------------------------|-------------|
| | | 最小min | 63 | 27 | | 2.30 | - | 0.35 | - | | - |
| | 500 | 最大max | - | 33 | 2.0 | 3.15 | 0.08 | 0.85 | 1.5 | 0.5 | 0.01 |
| 物理特性 Physical Characteristics | 密度 Density 8.05g/cm ³ | | | | | | | | | | |
| | 増点 Melting point 1288-1343℃ | | | | | | | | | | |
| 在常温下合金 的机械性能的 最小值 | 典 | 型机械性能 | | 抗拉强度 Rm N/mm ² | | 屈服强度 P0.2 N/m | | 延伸率 A5% | | 测试温度 Test ℃ | |
| | | 固溶处理 | | 1100 | | 790 | | 20 | | 常温 | |
| 特性 characteristic | | MONEL K5 度和硬度。 | | | | | | 虫性能, | 日是具有更 | 高的机械 | 强 |
| 金相结构 Metallographic structure | Monel500合金的组织为高强度的单相固溶体 | | | | | | | | | | |
| 耐腐蚀性 Corrosion resistance | | Monel k-500 海水中比铜排 可耐氢氟酸 [。] 性极佳,而且 空气中连续 Monel500合 | 基合金更 中为数极; 且孔蚀、) 工作的最; | 具耐蚀性。 少的重要材 应力腐蚀等 高温度一般 | Monel50 树之一。 作也很少发 在600°C | 0在浓度小 水腐蚀:M 现,腐蚀 左右,在和 | 、于85%的 lonel500 速度小于 高温蒸汽の | 的硫酸中都 合金在多 0.025mn 中,腐蚀 | B是耐蚀的 数水腐蚀物 h/a。高温J 速度小于0 | i:Monel k- 記下,不 寓蚀:Mone | 500是 仅耐蚀 |
| 应用范围 应用领域 Application | | 主要用于制动 的紧固件、3 | | | | | | | | 1、用于制道 | 自治的 |
| | M | | | | | | | | ~ | | |

Qingsen, one of the industry 's leading supplier of Truck Body Parts, Trailer Accessories and Commercial vehicle components since 2018.Our products cover more than 800 kinds which include Door Lock System.Hinges, Fasteners, Cargo Control, Door Seal, Door Retainer, Buckle, Roller, E-track, Winch, Buffer, Folding Step, Deck Ring etc. And can completelyserve for trucks, trailers, containers etc.we excel in providing our customers with the best in value by delivering the products you need.Our team strives for "extraordinary' in providing the truck body parts and trailer parts industry with the best in products and service which is unparalleled in the industry.when you need any parts related to a truck or trailer or container of anykind.Qingsen is your world-wide ONE-STOP SHOP. With more than 500suppliers and factories nationwide, we help you get the projects donequickly and correctly.

Q1: Can I have one or two samples for checking?

A: Yes, one free samples and freight collect, trial order is aslo welcome.

Q2: What's your lead time?

A: Depending on orders, usually 10~35 days

Q3: What countries have you exported to?

A: Worldwide!

Q4: Do you have MOQ ?

A: Depending on exact product, usually 500 units, no MOQ if goods in stock, most products list on Alibaba we have hundreds to thousands in stock.

Q5: Can you meet my requirements like print LOGO on the product, specific packaging, etc

A: Of course! we are a profesional factory, everything can go in you way!

Q6: Can I visit your company?

A: sure, any time at your convinience, please inform us before your visit

Q7: How is my product shipped? Will my product arrive on time?

A: By sea, by air or by express carriers (UPS, FedEx, TNT) transit time depends on freight rates.

Q8: What's terms of payment?

A: 30% T/T deposit, 70% balance before delivery.

- B: 30% T/T deposit, 70% balance against BL.
- C: 100% in advance, L/C at sight, Western Union/ Paypal for small amount payment.

E Suzhou Industrial PARK Qingsen Trading Co., Ltd.

🕓 +8613815258017 🔄 sales@qingsensz.com.cn 📀 specialalloysteels.com

Room 916, Xinghai International Building, No.28, Wansheng Street, Suzhou Industrial Park