



3" Welding C276 C22 C2000 B2 B3 C4 G3 G30 G35 Hastelloy X WN RF Blind Socket Weld Flange

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Qingsen
- Model Number: Hastelloy C-276
- Minimum Order Quantity: 1-2 ton
- Price: negotiable
- Packaging Details: carton box
- Delivery Time: 15-20 days
- Payment Terms: Western Union, MoneyGram, T/T



Product Specification

- Technique: Cold Rolled Hot Rolled
- Model Number: Inconel 600/601/602CA/617/625/713/718/738/X-750
- Surface: Bright
- Shape: Flange
- Series: Monel/Inconel/Incoloy/Hastelloy/Stainless Steel
- Surface Treatment: Galvanized
- Size: 1/4" To 24"
- Thickness: SCH10, SCH20, SCH30, STD, SCH40, SCH60, SCH80, SCH100 SCH120, SCH160, XS, XXS
- Highlight: 3" welding c276, welding c276 C22, G30 haynes c276



Product Description

3" Hastelloy Alloy C276 C-276 C22 C-22 C2000 B B-2 B-3 C-4 G-3 G-30 G-35 Hastelloy X WN RF Blind Socket weld Flange

ASME SB 564 Hastelloy C276 Orifice Flanges are used for measuring the flow rate of either liquids or gases in their respective pipelines. ASTM B564 Hastelloy B2 Weld Neck Flanges are generally used to stop one end of the flanged pipe, the opening of a pressure valve or an orifice valve.

Stand ard	PIPE FITTING Product Types	PIPE FITTINGS Size.
ASME B16.9	Long Radius Elbows, Long Radius Reducing Elbows, Long Radius Returns, Short Radius Elbows, Short Radius 180-deg Returns, 3D elbows, Straight Tees, Straight Crosses, Reducing Outlet Tees, Reducing Outlet Crosses, Lap Joint Stub Ends, Caps, Reducers	Size: 1/2"-48" Wall thickness: SCH5S-SCHXXS
ASME B16.28	Short Radius Elbows, Short Radius 180-deg Returns	Size: 1/2"-24" Wall thickness: SCH5S-SCHXXS
ASME B16.49	30° 45° 60° 90° Long Radius Short Radius Bend	Size: 1/8"-12" Wall thickness: SCH5S-SCHXXS
MSS- SP43	Long Radius Elbows, Straight and Reducing-on-the-Outlet Tees, Lap Joint Stub ends, caps, long radius 180 Degree returns, concentric reducers, eccentric reducers	Size: 1/2"-24" Wall thickness: SCH5S-SCHXXS
MSS- SP75	All Kind of Buttwelding Product or as Client's Drawing	As the Client's Demand
Material Stand ard	Nickel Alloy Forged fitting	ASTM/ASME SB 366 Alloy 200/UNS N02200, Alloy 800HT/Incoloy 800HT/UNS N08811, Alloy 400/Monel 400/UNS N04400, 904L/UNS N08904, Alloy 800/Incoloy 800/UNS N08800, Alloy C-2000/UNS N06200, Alloy 925/Incoloy 925/UNS N09925, Alloy C-22/UNS N06022, Alloy 201/UNS N02201, Alloy C-276/Hastelloy C- 276/UNS N10276, Alloy 625/UNS N06625, Nimonic 80A/Nickel Alloy 80A/UNS N07080, Alloy K-500/Monel K-500, Alloy 20/UNS N08020, Alloy 800H/Incoloy 800H/UNS N08810, Alloy 600/Inconel 600/UNS N06600, Alloy 31/UNS N08031, Hastelloy C-276/UNS N10276, Alloy 825/Incoloy 825/UNS N08825, Alloy 20/N08020
	Carbon Steel pipe fitting	ASTM/ASME SA 234 WPB
	Low Alloy Steel pipe fitting	ASTM/ASME SA 234 WP91, WP11, WP22, WP9,
	Duplex and Super Duplex Steel pipe fittings	ASTM/ASME SA 815 WPS31803, WPS32205, WPS32750, WPS32760, WPS32550
	Stainless Steel pipe fitting	



Hastelloy C-276

(UNS N10276/W.Nr.2.4819/NS336)

Hastelloy C-276 (UNS N10276/W.Nr.2.4819/NS336)															
化学成分 Chemical Composition	合金	%	Ni	Cr	Fe	Mo	C	Mn	Si	S	P	Co	V	W	
	哈C	最小vmin	余量	14.5	4	15									3
		最大max	余量	16.5	7	17	0.08	1	1	0.03	0.04	2.5	0.35	4.5	
	C276	最小vmin	余量	14.5	4	15									3
最大max		余量	16.5	7	17	0.01	1	0.08	0.03	0.04	2.5	0.35	4.5		
物理特性 Physical Characteristics	密度	Density				8.9g/cm³									
	熔点	Melting point				1325-1370°C									
在常温下合金 的机械性能的 最小值	典型机械性能		抗拉强度 Rm N/mm²		屈服强度 RP0.2 N/mm²		延伸率 A5%		布氏硬度 HB						
	固溶处理		690		283		40		-						
特性 characteristic	1.在氧化和还原状态下，对大多数腐蚀介质具有优异的耐腐蚀性。 2.出色的耐点腐蚀、缝隙腐蚀和应力腐蚀开裂性能。														
金相结构 Metallographic structure	C276为面心立方晶格结构。														
应用范围 应用领域 Application	Hastelloy C-276其它应用领域: 1.纸浆和造纸工业，如煮解和漂白容器 2.FGD系统中的洗涤塔、再加热器、湿汽风扇等 3.在酸性气体环境中作业的设备 and 元件 4.乙酸和酸性产品的反应器 5.硫酸冷凝器 6.亚甲二苯异氰酸盐 (MDI) 7.不纯硝酸的生产和加工														
<div></div> <div></div>															

Qingsen, one of the industry 's leading supplier of Truck Body Parts,Trailer Accessories and Commercial vehicle components since 2018.Our products cover more than 800 kinds which include Door Lock System.Hinges, Fasteners, Cargo Control, Door Seal, Door Retainer,Buckle, Roller,E-track, Winch,Buffer, Folding Step,Deck Ring etc. And can completelyserve for trucks,trailers, containers etc.we excel in providing our customers with the best in value by deliveringthe products you need.Our team strives for "extraordinary" in providingthe truck body parts and trailer parts industry with the best in productsand service which is unparalleled in the industry.when you need any parts related to a truck or trailer or container of anykind.Qingsen is your world-wide ONE-STOP SHOP. With more than 500suppliers and factories nationwide, we help you get the projects donequickly and correctly.

Q1: Can I have one or two samples for checking?

A: Yes, one free samples and freight collect, trial order is aslo welcome.

Q2: What's your lead time?

A: Depending on orders, usually 10~35 days

Q3: What countries have you exported to?

A: Worldwide!

Q4: Do you have MOQ ?

A: Depending on exact product, usually 500 units, no MOQ if goods in stock, most products list on Alibaba we have hundreds to thousands in stock.

Q5: Can you meet my requirements like print LOGO on the product, specific packaging, etc

A: Of course! we are a profesional factory, everything can go in you way!

Q6: Can I visit your company?

A: sure, any time at your convinience, please inform us before your visit

Q7: How is my product shipped? Will my product arrive on time?

A: By sea, by air or by express carriers (UPS, FedEx, TNT) transit time depends on freight rates.

Q8: What's terms of payment?

A: 30% T/T deposit, 70% balance before delivery.

B: 30% T/T deposit, 70% balance against BL.

C: 100% in advance, L/C at sight, Western Union/ Paypal for small amount payment.



Suzhou Industrial PARK Qingsen Trading Co., Ltd.



+8613815258017



sales@qingsensz.com.cn



specialalloysteels.com

Room 916, Xinghai International Building, No.28, Wansheng Street, Suzhou Industrial Park